

**BOSCH**

GSU3103/01-V01
GSU3103CH/01-V02
GSU3103GB/01-V03


GSU3103/02-V04
GSU3103CH/02-V05
GSU3103GB/02-V06

KÜHL-,GEFRIERGERÄTE
Gefrierschränke, Stand

07 4445
V01,V04
09 6572
V02,V05
09 6325
V03,V06

Ident - Nummern - Konstante
3740

Gebrauchsanweisung
51 9942
(D,GB,F,I,NL,N)




**BOSCH**

GSU3103/01-V01
GSU3103CH/01-V02
GSU3103GB/01-V03

GSU3103/02-V04
GSU3103CH/02-V05
GSU3103GB/02-V06

KÜHL-,GEFRIERGERÄTE
Gefrierschränke, Stand

Ident – Nummern – Konstante
3740



Pos.	V01-V03	V04-V06	
	Matsushita	Danfoss	
	DA 12 SE	NLY 13 K	
1	14 1556	14 1684	
2			
3	03 2035	15 1055	
4			
5	16 2549	15 0760	
6	05 8458	15 1072	
7			
8	11 1567	11 1567	
9	05 0166	05 0166	
10	15 2222		
11	08 8535	09 6212	
12	05 6008	05 6008	
13	35 0026		

TECHNISCHE DATEN / TECHNICAL DATA / DONNEES TECHNIQUES						
Verdichter/Compressor/Compresseur		Matsushita		Danfoss		
Typ/Type		DA 12 SE		NLY 13 K		
Förderleistung/Delivery/Débit		l/h	2250			2394
Anlaufstrom/Starting current/Cour de démarrage		A	8,7			11,3
Widerstand/Resistance/Résistance Ha/main/prin		Ω	12,0			11,0
Hi/aux		Ω	28,7			9,0
Temp.-Regler/Thermostat		Elektronisch				
Solltemperatur-Einstellung		°C	EIN AUS			
		-18	-15 -16			
		-22	-19 -20			
		-26	-23 -24			
"alarm"			-9 -14			
Füllmenge/Fill.quantity/Charge		R600	siehe Typenschild			
Anschlußwert/Conn.load/Puiss. connectée		W	120			
Heizung/Heater/Chauffage		Abtauheizung		Rinnenheizung		
Widerstand/Resistance/Résistance		Ω	173	6050 ± 730Ω		
Leistung/Power/Puissance		W	333	9,5		
Ventilator/Blower/Ventilateur						
Widerstand/Resistance/Résistance		Ω	340			
Widerstand NTC-Fühler		°C	kΩ	°C	kΩ	°C
		-1	17,3	-15	36,5	-20
		-9	26,2	-16	38,8	-23
		-14	34,5	-19	45,9	-24
Magnetventil/Magnetic valve/Electrovanne						
Widerstand/Resistance/Résistance		Ω				
Spannung/Voltage/Tension		V				